AI internet camera

100 100	Model: Ai-CAM		The main features
Trime framework register, specimens of pair framework in the second companies of the pair of the finding in time women as a second headers in a most and the finding in time women as a second headers in the second case as former and the pair of the second case as former and the control pairs in the second case as former and the control pairs in the second case as former and the control pairs in the second case as former and the case as a case and the case as former and the cas			• 355° rotation, privacy mode
The state of the s			•The image clear 、smooth , interlligent transmission plays to the limits od the network .
trains, low cost courts, both Blocks, more morted receiving, no doug Compared with E-24 time compensate absorbing, the risks are received provided in the East Association of the Compared with the Compared with E-24 time compensate absorbing, the risks are received by the Compared with E-24 time compensate absorbing, the Compared with E-24 time compensate absorbing, the Compared with E-24 time compensate absorbing, the Compared with E-24 time compensate absorbing to the Compared wit			Online firmware upgrade , synchronize update function
Specification Signor Acadesis, 1955. - 2.069 (1950x100), linear-bace - 1.069 (1950x100), linear-bace - 1.069 (1950x100), linear-bace - 1.069 (1950x100), linear-bace), filter-back (1950x10), linear-bace) - 1.069 (1950x100), linear-bace), filter-back (1950x10), linear-bace), stand-tempe - 1.069 (1950x100), linear-bace) -			quality, low code stream, local HD video, more smooth viewing, no drag. Compared with H.264 video compression algorithm, the bit
- PARTE (PROVISION), image clear - Black (See discussed 20.7). 2000000000000000000000000000000000000			Support Two-way voice talkback,remove echo ,suppresses noise
Heat Control description 870 - 28000 motions. IECUT security, the images clear in inginession and color clear in Digol Superior 240 with URBANIE Holysis Superior 240 with URBANIE Superior 240 wi			• Support Android, IOS.
Support 3.et Wire[0] F 100 L lb psg Support 3.et wire[0] F 100 Lb psg Supp			• 2.0MP (1920X1080), image clear
- Sont pank, filter meles information - Main SD and data (1984a) local storage , cloud storage - Sont pank, filter meles information are work - Sont pank, filter meles and distribution are work - Sont pank, filter meles and distribution are work - Sont pank, filter meles and distribution are work - Sont pank, filter meles and distribution of the pank pank pank pank pank pank pank pank			• IR led (the distance is 7m) 、 24hours monitor、IR-CUT switch, the image is clear in nightvision ,not color cast in Day
Shire SD cade Art (12048) boat trange, chool stronge Support Office after intelligent connection and devolution network Support Support of after an interest in			Support 2.4G Wi-Fi(IEEE802.11b/g/n)
Support Office code intelligent connection and distribution nativoid. *Support Descriptore, human detection, mention bracking planted forme. *Support Descriptore, human detection, mention bracking planted forme. *Support Descriptore, human detection, mention bracking planted forme. *Support Descriptore, human detection, mention bracking. *Support Descriptore, human detection, men			Smart push , filter useless information
Support per capture, harant detection, motion maching detects fance. **Inter**			Micro SD card slot (128GB) local storage , cloud storage
To To Specification S			Support QR code intelligent connection and distribution network
Natio processor			Support pet capture, human detection, motion tracking electric fence.
Main processor			the appearance is delicate , multicolor
Senor	Item		Specification
Image season	Main processor	SOC	T3IN
	Image sensor	Sensor	1/3"colourful CMOS sensor
Visal Angle HS 7-VAS - DIOO* DIOX DI		lens	M12,f: 3.6mm,F2.0, 2.0MP
Part		Visual Angle	H85°; V48°; D100°
Audio AAC Vide Compression I1265 frequency 5981z, 6981z Video image fame 15fps Image Size 1920*1080P IR distance IRCUT, 6ges led (85fmm)7M WFT 2.46 WFR[EESEQ.11 beg/n]x, built-on antenna Internet Support protocol TCFIP, UDPIP, DHCP, RTMP, MUTP Support IP address dynamic IP address Alarm notion detection Alarm function notion detection Alarm function APP Smart Smart function PVZ FIZ angle II (0° – 35%; V(20° – 90°) Port SD card det Micro SD (126G8) button one LED indicate white light (power/network signal function indicator) Video storage mode Micro SD card slot (128G8) local storage, cloud storage Installation method celling or wall Work conviconment -10° – 45° / 10% – 80% Colour Colour Slocal Avhila; pry, yellow, puple, pink con optional Specification Weight About 180g		mini illumination	0.01Lux
Vide Compression H.265 frequency 50Hz, 60Hz Image Size 1920*1000P IR distance BCUT , 6yes Ird (850ms),7M WFF 2.40 WFF(EEE802_11bg/m), built-in anterma Support Peadross dynamic Pradfress Alarm detection motion detection alsern linkage Support veloch covered_asond alarm Alarm notice AFF Smart Smart (inction mart push , per capture, human detection , motion tracking PTZ PTZ angle H.0° - 555°; W.20° - 99°) Port SD card slot Micro SD (1250B) Button one LED indicate white light (power/network signal function indicator) Video atorage mode Micro SD card slot (1280B) local storage , cloud storage LED indicate white light (power/network signal function indicator) Video atorage mode Micro SD card slot (1280B) local storage , cloud storage LED indicate white light (power/network signal function indicator) Video atorage mode Micro SD card slot (1280B) local storage , cloud storage LED indicate white light (power/network signal function indicator) Video atorage mode Micro SD card slot (1280B) local storage , cloud storage LED indicate video Colour Sales white page, yellow, puple, pink can optional Sales white page, yellow, puple, pink can optional Sales white Specification Weight Power/network	Audio	put in/out	Two-way voice talkback(built-in mic &hom)
Frequency Video image frame 15fps 1mage Size 1920*1080P 1R distance 18CUT 6pcs led (850m),7M WET 2.4G WEFRIEERS02.11b/gsh], built-in antenna WET 2.4G WEFRIEERS02.11b/gsh], built-in antenna Support protocol TCPIP, UDPIP, DHCP, RTMP, MUTP Support Paddress dynamic IP address Alarm detection motion detection alarm linkage Support video record , sound alarm Alarm notice APP Smart Smart function must push , per capture, human detection , notion tracking PTZ PTZ angle 11(0°-355°); V(20°-90°) Power One pea Micro USB pert DC SV/IA SD card slot Mero SD (128GB) hutton one LID indicate white light (powernetwork signal /function indicator) Video storage mode Micro SD card slot (128GB) local storage , cloud storage Installation method ceiling or wall Storage environment -10°C-45°C/10°s - 80°s Specification Specification Specification Weight About 180g		Audio Compression	AAC
Nideo Image fame 15fps 1920*1080P 1R distance 1920*1080P 1P sadress 24G WFF(IEE802.11b/gh), buils-in antenna 24G WFF(IEE802.11b/gh	Video	Vide Compression	H.265
Internet Redistance PCUT, 6pec led (850mm).7M WFT 2.4G WFF(EEE802.11b/gin), bealt-in antenna Support protocol TCPIP, UDP/IP, DHCP, RTMP, MUTP Support Praddress dyramic IP address Alarm detection motion detection Alarm inkage Support video record, sound alarm Alarm notice APP Smart Smart inkage amort push , pet capture, human detection , motion tracking PTZ PTZ angle H (0° – 355% Vc.20° – 90°) Power One pes Micro USB port, DC SVIA Port SD card slot Micro SD (128GB) button one LED indicate white light (power/network signal /function indicator) Video storage mode Micro SD card slot (126GB) local storage cloud storage LED indicate white light (power/network signal /function indicator) Video storage mode Micro SD card slot (126GB) local storage , cloud storage Let midlation method ceiling or wall Environment -10°C-45°C (10% – 80% Storage environment -20°C-60°C (0%-90%) Slock WV.411 27mm*72mm*11.5 mm Specification Weight About 180g		frequency	50Hz, 60Hz
Internet IR distance IR (distance) IR (distance)		image frame	15fps
Internet Support protocol TCP/IP, UDP/IP, DHCP, RTMP, MUTP		Image Size	1920*1080P
Internet Support IP address dynamic IP address Alarm Alarm Alarm alarm inkage Support video record sound alarm Alarm notice APP Smart Smart Snart unterion Smart Braderss APP Pover One pes Micro USB port, DC SV/IA Button One LED indicate white light (power/network signal /function indicator) Video storage mode Installation method ceiling or wall Work environment Storage environment Specification Veight About 180g Territy, UDP/IP, DHCP, RTMP, MUTP Address Aynamic IP address Appendix II ad		IR distance	IRCUT, 6pes led (850nm),7M
Alarm detection motion detection Alarm linkage Support video record ,sound alarm Alarm notice APP Smart Smart Smart function smart push , pet capture, human detection , motion tracking PTZ PTZ angle H (0° - 355°); V(-20° - 90°) Power One pes Micro USB port ,DC 5V/1A SD card slot Micro SD (128GB) Dutton one LLED indicate white light (power/network signal /function indicator) Video storage mode Micro SD card slot (128GB) local storage , cloud storage Installation method ceiling or wall Work cnvironment -10°C-45°C /10% - 80% Storage environment -20°C-60°C/0%-90% Colour Colour Storage mode Micro SD (200w, purple, pink can optional size(LWASH) 72mm*12.5mm Weight About 180g	Internet	WIFI	2.4G WIFI(IEEE802.11b/g/n), built-in antenna
Alarm detection motion detection alarm linkage Support video record ,sound alarm Alarm notice APP Smart Smart function smart push , pet capture, human detection , motion tracking PTZ PTZ angle H (0° - 355°); V(20° - 90°) Pover One pes Micro USB port, DC 5V/1A Port SD card slot Micro SD (128GB) button one LED indicate white light (power/network signal /function indicator) Video storage mode Micro SD card slot (128GB) local storage , cloud storage Installation method ceiling or wall Work environment -10°C-45°C /10% - 80% Environment Specification Weight About 180g About 180g		Support protocol	TCP/IP、UDP/IP、DHCP、RTMP、MUTP
Alarm linkage Support video record ,sound alarm Alarm notice APP Smart Smart Smart function smart push , pet capture, human detection , motion tracking PTZ PTZ angle H (0° ~ 355°); V(-20° ~ 90°) Power One pcs Micro USB port ,DC 5V/IA Port SD card slot Micro SD (128GB) button one LED indicate white light (power/network signal /function indicator) Video storage mode Micro SD card slot (128GB) local storage , cloud storage Installation method ceiling or wall Environment Jore—45°C /10% ~ 80% Colour Colour Slack ,white,grey , yellow , purple , pink can optional Specification Smart function indicator 20mm*72mm*115.5mm Meright About 180g		Support IP address	dynamic IP address
Alam notice APP Smart Smart function smart push , pet capture, human detection , motion tracking PTZ PTZ angle H (0° ~355°); V(-20° ~90°) Power One pes Micro USB port ,DC 5V/IA Port SD card slot Micro SD (128GB) button one LED indicate white light (power/network signal /function indicator) Video storage mode Micro SD eard slot (128GB) local storage , cloud storage Installation method ceiling or wall Work environment -10°C-45°C /10% ~80% Storage environment -20°C-60°C/0%-90% Colour Colour Storage mode Micro SD eard slot (128GB) port pink can optional Specification Storage environment size(LSWRI) 72mm*72mm*115.5mm Weight About 180g		Alarm detection	motion detection
Smart Smart function smart push , pet capture, human detection , motion tracking PTZ PTZ angle H (0° ~355°); V(-20° ~90°) Power One pes Micro USB port ,DC 5V/IA SD card slot Micro SD (128GB) button one LED indicate white light (power/network signal/function indicator) Video storage mode Micro SD eard slot (128GB) local storage , cloud storage Installation method ceiling or wall Work environment + 10°C-45°C /10% ~80% Colour Colour Storage environment 20°C-60°C/0%-90% Specification Specification Weight About 180g	Alarm	alarm linkage	Support video record ,sound alarm
PTZ angle H (0° ~ 355°); V(-20° ~ 90°) Power One pcs Micro USB port ,DC 5V/IA SD eard slot Micro SD (128GB) button one LED indicate white light (power/network signal /function indicator) Video storage mode Micro SD eard slot (128GB) local storage , cloud storage Installation method ceiling or wall Work environment -10°C-45°C /10% - 80% Storage environment -20°C-60°C/0%-90% Colour Colour black ,white,grey , yellow , purple, pink can optional Specification Weight About 180g			APP
Port Power One pes Micro USB port ,DC 5V/IA SD card slot Micro SD (128GB) button one LED indicate white light (power/network signal /function indicator) Video storage mode Micro SD card slot (128GB) local storage , cloud storage Installation method ceiling or wall Work environment -10°C-45°C /10% - 80% Storage environment -20°C-60°C/0%-90% Colour Storage environment size(LxWxH) 72mm*115.5mm Weight About 180g			
Port SD card slot Micro SD (128GB) button one LED indicate white light (power/network signal /function indicator) Video storage mode Micro SD card slot (128GB) local storage , cloud storage Installation method ceiling or wall Work environment -10°C-45°C /10% ~ 80% Storage environment -20°C-60°C/0%-90% Colour Colour black, white,grey , yellow , purple , pink can optional Specification Weight About 180g	PTZ	PTZ angle	
button one LED indicate white light (power/network signal /function indicator) Video storage mode Micro SD card slot (128GB) local storage , cloud storage Installation method ceiling or wall Work environment -10°C45°C /10% ~ 80% storage environment -20°C-60°C/0%-90% Colour Colour black ,white_grey , yellow , purple , pink can optional Specification Weight About 180g	Port		
LED indicate white light (power/network signal /function indicator) Video storage mode Micro SD card slot (128GB) local storage , cloud storage Installation method ceiling or wall Work environment -10°C-45°C /10% ~ 80% storage environment -20°C-60°C/0%-90% Colour Colour black ,white,grey , yellow , purple , pink can optional size(LxWxH) 72mm*72mm*115.5mm Weight About 180g			Micro SD (128GB)
Video storage mode Micro SD card slot (128GB) local storage , cloud storage Installation method ceiling or wall Work environment -10°C-45°C /10% ~ 80% storage environment -20°C-60°C/0%-90% Colour Colour black ,white_grey , yellow , purple , pink can optional Specification Weight About 180g			
Installation method ceiling or wall			
Work environment			
Environment storage environment -20°C-60°C/0%-90% Colour Colour black ,white,grey, yellow, purple, pink can optional size(LxWxH) 72mm*72mm*115.5mm Weight About 180g			
Colour Colour black ,white,grey, yellow, purple, pink can optional Specification size(LxWxH) 72mm*72mm*115.5mm Weight About 180g			
Specification size(LxWxH) 72mm*115.5mm Weight About 180g			
Specification Weight About 180g			
Certification Certification CE,FCC,RoHS,WEEE	Specification		
	Certification	Certification	CE,FCC,RoHS,WEEE